

**Document of Performance**  
**According to Regulation (EU) 305/2011**

Aduro 15		DoP No: 15 0001
Roomheater burning solid fuel <u>without</u> hot water supply. EN 13240:2001/A2:2004/AC:2007		
Aduro AS, Beringvej 17, DK-8361 Hasselager, Denmark. <a href="http://www.aduro.dk">www.aduro.dk</a> , <a href="mailto:info@aduro.dk">info@aduro.dk</a> , Tel.: +45 70274703.		
System 3 of assessment and verification of constancy of performance of the construction product: Internal quality security system in combination with external production control.		
<p>Rhein-Ruhr Feuerstätten Prüfstelle GmbH, Im Lipperfeld 34 b, D-46047 Oberhausen, notified body number: 1625 and Teknologisk Institut, Kongsvang 29, DK-8000 Aarhus, notified body number: 300.</p> <p>performed the determination of the product type on the basis of type testing under system 3 and <u>issued test report</u>: RRF- 40 14 3538 300-ELAB-2060-NS</p>		
Declared performance		
<b>Harmonized technical specification</b>	EN 13240:2001/A2:2004/AC:2007	
<b>Essential characteristics</b>	<b>Performance</b>	
<b>Fire safety</b>		
Reaction to fire	A1	
Distance to combustible materials	Minimum distances, in mm	
Distance marked with * is for installation with isolated pipe	rear = 200/*120 sides = 340 front = 1200	
Risk of burning fuel falling out	Pass	
<b>Emission of combustion products</b>	CO[0.07 %]	
<b>Surface temperature</b>	Pass	
<b>Electrical safety</b>	NPD	
<b>Cleanability</b>	Pass	
<b>Maximum water operating pressure</b>	NPD	
<b>Flue gas temperature at nominal heat output</b>	T [329 °C]	
<b>Mechanical resistance (to carry a chimney/flue)</b>	NPD	
<b>Thermal output</b>		
Nominal heat output	6,5kW	
Room heating output	6,5 kW	
Water heating output	"" kW	
<b>Energy efficiency</b>	$\eta$ [78 %]	

Signed for and on behalf of the manufacturer by:

Christian Skovbo, CEO, Aduro AS  
Hasselager, 16-06-2014

